

SEAMASTER SILK PRO EASY WASH FINISH 7500G

1.9

Rev 07

18/02/2025



Description

Seamaster Silk Pro Easy Wash Finish 7500G is a satin wall finish for interior surfaces. It is washable with good adhesion, good alkaline and fungus resistance. It is a low odor, Zero VOC, APEO free and Formaldehyde free product.

Recommended Use

As a Specially formulated for protection and decoration of interior masonry and other surfaces such as plaster wall, cement, gypsum board, brickwork, hard and soft boards and on appropriately primed wood surfaces.

Surface Preparation

New Masonry Surface:

It is crucial that ample time is allowed for the concrete /plaster surfaces to dry out. High moisture content is a common cause for premature paint failures, such as blistering, discolouration, etc. Concrete/plaster are alkaline in nature and together with the presence of salts and moisture may cause paint systems to fail prematurely. Masonry surfaces must be reasonably dry and free from oil / grease and other contaminants before an appropriate alkali resistance sealer is applied.

Old Unpainted/Previously Painted Masonry Surface:

Surface must be dry and free from any structural damaged and cracks. Wash the surface to remove any stains, debris and powderiness before application with Seamaster Silk Pro Easy Wash Finish 7500G.

Certification

It complies with requirements under:

- SIRIM Eco-Label Mark
- Certified to Malaysian Standard MS 903:1984
- Recognised as a Halal product by LPPOM (MUI) Indonesia

Physical Properties

Vehicle Type	Modified Vinyl Acetate
Pigmentation	Mineral extenders, pigments and additives
Solvent	Water
Density (kg/litre)	1.20 ~ 1.40 (varies depending on colours)
Volume Solid	Approximately 30%
Drying Time at (27 ± 2°C & RH : 80 ± 5%)	Touch Dry ≤ 30 minutes Hard Dry ≤ 1 hour
Dry Film Thickness	25 ~ 30 microns per coat
Recoating Interval	≥ 3 hours
Theoretical Coverage	10 ~ 12 m²/litre (Actual coverage is dependent on substrate condition)
Colours	Varies. Refer to colour card
Gloss at (85° head)	15-20 %
Finish	Satin Finish
Shelf Life	36 months at 27 ± 2°C in full sealed containers
Pot Life	N/A
Storage Condition	Air tight, store in dry and cool condition
Packing	1 litre, 5 litres & 15 litres
Application Temperature	5°C to 40°C

Application Method

Paint Preparation	Ready for use after thoroughly stirring. However, if thinning is required, not more than 5% of water may be added for the first coat. For best result, thinning is not recommended for the subsequent coats.
Mixing Ratio	N/A

Recommended Coating System

Sequence	Product Reference	No of Coat(s)	Dry Film Thickness
Primer	Seamaster Base Coat Acrylic Wall Sealer (Water Based) (Interior) 1600	1	15 ~ 20 microns
Finish Coat	Seamaster Silk Pro Easy Wash Finish 7500G	2	50 ~ 60 microns

Health and Safety

This product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Product Liability

The Seller warrants the product to be free from manufacturing defects in material and workmanship. The Seller's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited at the Seller's option, to either replacement of products not conforming to this warranty or credit to the Buyer's account in the invoiced amount of the non-conforming products.

The Seller makes no other warranties concerning this product. No other warranties, either express or implied, or satisfactory, and as warranties or merchantability or fitness for a particular purpose, shall apply. In no event shall the Seller be liable for consequential or incidental damages. Any recommendations or suggestion relating to the use of the products made by the Seller, whether in its technical limitation, or in response to specific inquiry, or otherwise, is based on data believed to be reliable, however, the products and information are intended for Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use, and it shall be deemed that the Buyer has done so, at its sole discretion and risk. Variation in environment changes in procedures of use or extrapolation of data may cause unsatisfactory results.